Get hold of some LIGHTNING...





1984 Limited Edition Hurst/Olds

The power to move you. 180-horse V8, 5-liter displacement. (That's 307 cubic inches). With a compression ratio of 8 to 1, a Rochester 4MV Quadrajet Carb, high-performance cam shaft and low-restriction dual outlet exhaust, it develops 245 lbs-ft of torque at 3200 revs. Coupled through the 4-speed automatic, with the Hurst Triple Shifter, and the 3.73:1 differential, this machine gets you to 60 mph in 9.8 seconds on the test track. Power you can feel.

LIGHTNING under control... an experience you won't forget





Underneath, there's a lot more.

First, there's a full set of 15" chrome & silver superstock wheels. Special steering gear, higher rate springs, larger diameter stabilizer bar, superlift air shock absorbers. Rubber isolated body frame mounts. And all the modifications required by the special transmission and low-restriction dual exhaust.

Hurst/Olds Package—Includes Silver Metallic and Black special paint scheme with Red and Black accent stripes on Upper Sides and Front-End Panel, Blacked-out Bumpers, Bumper Guards, Headlamp Doors, Tall Lamp and Backup Lamp Bezels with Black and Bright Grille, Amber Park/Turn Lamp lenses, Chrome and Silver Super Stock Wheels with Red accent stripe, Black Front Lower Air Dam, Silver Deck Lid Spoiler, Non-functional Hood Scoop and Bumper Rub Strip Moldings. Includes all Calais interior features such as Reclining Bucket Front Seats, Outside Mirrors Silver, Sport Console, Firm Ride and Handling package plus Superliff Air Shock Absorbers, Custom Sport Steering Wheel, P215/65R15 Goodyear Eagle GT Tires, Instrument Panel Rallye Cluster and Tungsten Halogen Headlamps, 5.0-liter V8 Engine (LV2) with high-performance camshaft and dual-outlet exhaust system; 4-Speed Automatic Overdrive Transmission (MXO) with special Hurst "Lightning Rod" shifters and a 3.73 Axle Ratio.

Lightning control.The Hurst Lightning Rods automatic shifter provides both automatic transmission ease and driver manual control of upshift and downshift. Select Park, Reverse, Neutral, Drive, or Overdrive as you would with the original equipment automatic overdrive transmission. Or use the "Lightning Rods" to take control of upshift/ downshift timing.

With the main control stick in D (Drive), use the center stick to downshift to "2nd" (or back up to Drive). Once you're in 2nd, use the right-hand stick to downshift from 2nd to 1st (or back up to 2nd).

Here's the cockpit.

It's all right there. Speedometer, trip odometer, tachometer, fuel and oil pressure gauges and ammeter. All the information you need for driving.


Plus a few extras. Sport steering wheel—of course—and reading lights are part of the package. And the front bucket seats recline nicely but are really built for driving.






1984 Limited Edition Hurst/Olds







There is a special feel in an Oldsmobile

Specifications:

ENGINE	
Type V-8, iron block and heads aluminum intake manifolo	1
Bore x stroke	
Displacement	
Carburetion 1 x 4 Rochester 4MV Quadraje	
Emission controls monolythic bed catalytic	;
converter, feedback fuel-air-ratio	
control, EGR, auxiliary air pump Valvetrain pushrods, overhead valves	
hydraulic lifters	3
Power (SAE net) 180 bhp @ 4000 rpm	1
Torque (SAE net) 245 lbs-ft @ 3200 rpm Exhaust system low restriction dual outlet mufflers	
Fuel requirementUnleaded	1
DRIVETRAIN	
Transmission 4-spd. automatic THM-200-4R with	
lockup torque converter 2400 rpm stall speed	
Final drive ratio 3.73:1 (limited slip optional)	
Transmission gear ratios 1 2.74	
II 1.57	
III 1.00 IV .67	
WOT upshift 1-2:5200 rpm, 2-3:4900 rpm	
3-4:4400 rpm	
SUSPENSION Front independent, unequal length control arms	
coil springs, anti-sway bar (1.25 in. diameter)
Rearrigid axle, 4 trailing links, coil springs anti-sway bar (.875 in. diameter	
STEERING	
Type recirculating ball, power assisted Ratio	
Turns lock-to-lock	
BRAKES	
Front	
WHEELS AND TIRES	
Wheel size	
Super Stoc Tire make and size Goodyear Eagle GT Stee Belted Radial, P215/65R x 15 RW	el
DIMENSIONS AND CAPACITIES Wheelbase108.1 in	
Length	
Width71.6 in	1.
Curb weight	
Weight distribution F/R	
CHASSIS/BODY	
Type full length frame with rubber isolated bod Body material welded steel stamping	
INTERIOR	
Front seats reclining bucket, clot or vinyl upholster	y
Gauges 85 mph (140 kph) speedomete	r,

oil pressure, fuel level, water temperature, voltage.

with trip odometer, tachometer,